



ECOLANDER *Rapid*®

4x4/SUV | ON & OFF ROAD

DIAMETER	SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	TREAD DEPTH (MM)
15 INCH	215/75R15LT	106/103	S	6J	11.6
	225/75R15LT	108/104	S	6J	11.6
	235/75R15LT	110/107	S	6½J	11.6
	255/70R15LT	113/110	S	7½J	11.6
	31×10.50R15LT	109	S	8½J	11.6
16 INCH	215/70R16	99	T	6½J	9.7
	215/85R16LT	115/112	S	6J	11.6
	225/70R16	101	T	6½J	9.7
	225/75R16LT	115/112	S	6J	11.6
	235/70R16	104	T	7J	9.7
	245/70R16	106	T	7J	9.7
	245/70R16	111	T	7J	9.7
	255/70R16	109	T	7½J	9.7
	265/70R16	111	T	8J	9.7
	265/70R16LT	121/118	R	8J	11.6
	265/75R16LT	123/120	S	7½J	11.6
	285/75R16LT	126/123	R	8J	11.6
17 INCH	245/75R17LT	121/118	S	7J	11.6
	265/65R17	110	T	8J	9.7
	265/70R17	113	T	8J	9.7
	265/70R17LT	121/118	S	8J	11.6
	275/65R17	113	T	8J	9.7
	285/70R17LT	121/118	S	8½J	11.6
	305/70R17LT	121/118	R	9J	11.6
	315/70R17LT	121/118	R	9½J	11.6
18 INCH	275/65R18LT	123/120	S	8J	11.6